File: phos_status.doc
Last updated: 10 June 2008

Readout sub-detector status

PHOS

Local Trigger Crate: **C27B**

Table of contents

L0
BUSY
TTC optical connections
Prepulse
L1 Message format

Trigger Questionnaire status: Additional information requested
Questionnaire last updated: 20 February 2007

L0

L0 over TTC option (Yes/No): **Yes**

L0 cable outputs

Number of L0 connections (only for testing?): **1**

Output $L0_1$:
- Cable number: **4031021**
- Cable length: **?**

BUSY

BUSY cable inputs

Number of BUSY connections: **1**

Input BUSY1:
- Enable (Yes/No): **Yes**
- Cable number: **18639**
- Cable length: **?**

Input BUSY2:
- Enable (Yes/No): **No**
- Cable number: **18029**
- Cable length: **?**

Fanin board (Yes/No): **No**

TTC optical connections

Number of optical connections: **2**
Length of the optical patchcord: **2.2m**
Length of the optical cable: **?**
Optical coupler used (Yes/No): **Yes**
Optical patch-panel slot: **4**
Optical patch-panel connector: **1**

Prepulse

Prepulse used (Yes/No): **Yes**
Delay setting D (TTCvi): **3422**
Lead time to the calibration L0 [(3556-D-54) x 25ns]: **2µs**

L1 Message format

(First word only/All five words): **First word only**