File: pmd_status.doc
Last updated: 15 February 2008

Readout sub-detector status

PMD

Local Trigger Crate: **C26B**

Table of contents

L0
BUSY
TTC optical connections
Prepulse
L1 Message format

Trigger Questionnaire status: Additional information requested
Questionnaire last updated: 1 February 2007

L0

L0 over TTC option (Yes/No): **No**

L0 cable outputs

Number of L0 connections: **1**

Output $L0_1$:
Cable number: **7502**
Cable length: **30m**

Fanout board (Yes/No): **No**

BUSY

BUSY cable inputs

Number of BUSY connections: **1**

Input BUSY1:
Enable (Yes/No): **Yes**
Cable number: **12386**
Cable length: **30m**
Input BUSY2:
Enable (Yes/No): **No**

Fanin board (Yes/No): **No**

TTC optical connections

Number of optical connections: **1**
Length of the optical patchcord: **2.2m**
Length of the optical cable: : **?**
Optical coupler used (Yes/No): **No**
Optical patch-panel slot (05/3, 4): **5**
Optical patch-panel connector: **3**

Prepulse

Prepulse used (Yes/No): **Yes**
Delay setting D (TTCvi): **3422**
Lead time to the calibration L0 [(3556-D-54) x 25ns]: **2µs**

L1 Message format

(First word only/All five words): **All five words**