File: trd_status.doc
Last updated: 27 September 2007

Readout sub-detector status

TRD

Local Trigger Crate: **C26T**

Table of contents

L0
BUSY
TTC optical connections
Prepulse
L1 Message format

Trigger Questionnaire status: Additional information requested
Questionnaire last updated: 31 January 2007

L0

L0 over TTC option (Yes/No): **Yes**

L0 cable outputs

Number of L0 connections: **2**

Output $L0_1$:
- Cable number: **17898**
- Cable length: **?**

Output $L0_2$:
- Cable number: **Not connected**
- Cable length: **?**

Fanout board (Yes/No): **No**

BUSY

BUSY cable inputs

Number of BUSY connections: **2**

Input BUSY1:
- Enable (Yes/No): **Yes**
- Cable number: **18030**
- Cable length: **?**

Input BUSY2:
- Enable (Yes/No): **Yes**
- Cable number: **18032**
- Cable length **?**

Fanin board (Yes/No): **No**

TTC optical connections

Number of optical connections: **2**
Length of the optical patchcord: **1.8m**
Length of the optical cable: **10m**
Optical coupler used (Yes/No): **Yes**
Optical patch-panel slot: **5**
Optical patch-panel connector (1, 2): **1, 2**

Prepulse

Prepulse used (Yes/No): **No**
Delay setting D (TTCvi): **3422**
Lead time to the calibration L0 [(3556-D-54) x 25ns]: **2µs**

L1 Message format

(First word only/All five words): **All five words**