File: zdc_status.doc
Last updated: 15 February 2008

Readout sub-detector status

ZDC

Local Trigger Crate: **C26T**

Table of contents

L0
BUSY
TTC optical connections
Prepulse
L1 Message format

Trigger Questionnaire status: Additional information requested
Questionnaire last updated: 30 January 2007

L0

L0 over TTC option (Yes/No): **No**

L0 cable outputs

Number of L0 connections: **2**

Output $L0_1$:
- Cable number: **17689**
- Cable length: **100m**

Output $L0_2$:
- Cable number: **17883**
- Cable length: **10m**

Fanout board (Yes/No): **No**

BUSY

BUSY cable inputs

Number of BUSY connections: **2**

Input BUSY1:
- Enable (Yes/No): **Yes**
- Cable number: **17884**
- Cable length: **100m**

Input BUSY2:
- Enable (Yes/No): **Yes**
- Cable number: **17886**
- Cable length: **10m**

Fanin board (Yes/No): **No**

TTC optical connections

Number of optical connections:	**3**
Length of the optical patchcord:	**1.8m**
Length of the optical cable: :	**2: 100m; 1: 10m**
Optical coupler used (Yes/No):	**No**
Optical patch-panel slot (to CR4):	**9**
Optical patch-panel connector:	**1,2**
Optical patch-panel slot (to C23*):	**5 (connectors 5 and 6)**
Optical patch-panel connector:	**5**

* Connected to C23, slot 09, connectors 4 and 5, shared with MTRG)

Prepulse

Prepulse used (Yes/No):	**No**
Delay setting D (TTCvi):	**3422**
Lead time to the calibration L0 [(3556-D-54) x 25ns]:	**2µs**

L1 Message format

(First word only/All five words):	**All five words**